



# BRUSHBUSTER MT

STEEL GOOSENECK COVERED TOP STOCK TRAILER WITH HIGH BRUSH FENDERS.

## AVAILABLE SIZES

- 16' x 6'8" x 6'6" w/ 2-5200# axles, 15" radial tires & 6-hole wheels
- 16' x 6'8" x 6'6" w/ 2-6000# axles, 16" radial tires & 8-hole wheels
- 20' x 6'8" x 6'6" w/ 2-6000# axles, 16" radial tires & 8-hole wheels
- 20' x 6'8" x 6'6" w/ 2-7000# axles, 16" radial tires & 8-hole wheels
- 24' x 6'8" x 6'6" w/ 2-7000# axles, 16" radial tires & 8-hole wheels
- 24' x 6'8" x 6'6" w/ 2-8000# axles, 16" radial tires & 8-hole wheels
- 28' x 6'8" x 6'6" w/ 3-6000# axles, 16" radial tires & 8-hole wheels
- 28' x 6'8" x 6'6" w/ 3-7000# axles, 16" radial tires & 8-hole wheels
- 28' x 6'8" x 6'6" w/ 2-8000# torflex axles, 16" radial tires & 8-hole wheels

## DIMENSIONS

- 7' gooseneck length
- 6'8" width
- 6'6" standard height

## UNDERCARRIAGE

- Spring axles w/ greasable hubs
- Forward self adjusting brakes on all wheels
- Radial Tires on silver modular wheels w/ chrome center caps
- Spare tire rack on GN

## COUPLER & JACKS

- Adjustable stem w/ set screw & pin w/ 2-5/16" coupler & safety chains w/ hooks
- Emergency breakaway system: switch, cable & battery box complete w/ battery & charger
- 12K Single speed drop-leg jack

## LIGHTS & ELECTRICAL

- DOT required lighting

## DESIGN FEATURES

- Heavy duty gooseneck structure w/ 8" box channel upright
- All steel frame w/ 1" x 3" tubing sides
- 1" pipe runners on side above tubing sides and on roof
- 1 5/8" formed steel wall post and roof crossmember
- 4" Channel crossmembers on 48" centers
- Galvaneal 20 gauge steel roof
- Low profile 6" radius galvanized roof
- Chrome trim w/ colored vinyl insert
- 10 gauge steel formed high brush fenders
- Pin striping
- 2"x 8" Treated wood floor
- Greasable exterior hinges

- Tag bracket
- 6" radius formed bonnet enclosed in galvanized steel
- Galvaneal 20 gauge steel roof
- Automotive grade 12 step paint process
- 1 5/8" Pipe bumper

## LOAD AREA EQUIPMENT

- Side access door on curb side above fenders
- Heavy duty anti climb center gate w/ hold back & spring loaded slam latch (24' & 28' lengths have 2; 32' has 3) made of 1" pipe steel on 3" centers (interior and exterior latch release)
- Heavy Duty double swing in & out butterfly rear gates w/vertical and horizontal latching system
- Heavy Duty center gate w/ hold back & spring loaded slam latch (24' & 28' lengths have 2)

CM Trailers reserves the right to make any change in paint, design, or construction as necessary for engineering. All visual representation, specification, and dimensions are based on the latest product information available at the time of publication. Some of the equipment shown or described is available at extra cost. At no time will any of the material or information contained in this publication have any justifications for resolving disputes. All axle ratings will be listed as per FMVSS 120, Section 5.1 states, the maximum load rating of the tires and rims fitted to an axle shall not be less than the GAWR specified on the certification label.